PROFESSIONAL · BULLET

SPC-BLP05-F28-A2-G1

5 MP Bullet Camera

AI Lite WDR 5MP 30fps Alarm, Audio, SD Slot, Reset ,4 Array IR POE in&out, IP67, Metal

5 MP · 2.8-12mm · 30 fps · PoE in/out



5 MP	1/2.7" Progressive Scan CMOS	2.8–12 mm	Up to 30 m	H.265 / H.264	PoE in/out	ONVIF Profile S/G/T, RTSP	IP67
Resolution	Image Sensor	Lens	IR Range	Compression	PoE	ONVIF	Protection

EDGE AI ANALYTICS

PROTECTION
Reduce nuisance alarms

- Human & vehicle classification [P]
- Perimeter intrusion [P]
- Line crossing [P]

OPERATIONAL INTELLIGENCE
Turn video into insight

IDENTIFICATION
Find what matters faster

- Face detection [P]

Analytics availability and simultaneous execution may vary by model, firmware and deployment architecture.

WHERE IT WORKS BEST

General security coverage	Perimeter and movement verification	Incident evidence	Outdoor Perimeter	Entrances	Warehouses

OPEN INTEGRATION
Camera and edge-intelligence layer. Recorder retention, Eye365 Smart Search, LPR365 workflows and MERGE365 integrations are selected as separate system roles.

ONVIF Profile S/G/T, RTSP

PROFESSIONAL TECHNICAL PRODUCT DATA

SPC-BLP05-F28-A2-G1

5 MP Bullet Camera



1. CAMERA & IMAGING

Image sensor	1/2.7" Progressive Scan CMOS
Effective pixels	5 MP
Minimum illumination	Color 0.003 lux @ F1.6 (AGC ON); B/W 0 lux @ IR ON
Day / Night	Full Color Mode / Day Night Mode / Schedule
Backlight compensation	Off/On (5 Zone)
Wide dynamic range	DWDR
Digital noise reduction	3D DNR
Privacy masking	Off/On (4 Zone, Rectangle)
Electronic shutter	1/5 ~ 1/20,000 s
IR range	Up to 30 m
AI / function profile	AI Lite profile

2. LENS

Lens type	Fixed
Focal length	2.8–12 mm
Aperture	F No. 1.8(W)-3.3(T)
Field of view	Horizontal: 79°, Vertical: 56°, Diagonal: 106°
Min. object distance	2.0m

4. STORAGE, AUDIO & ALARM

On-board storage	Micro SD slot, up to 256GB
Alarm I/O	1 input, 1 output
Audio I/O	1 input, 1 output
Hardware reset	YES
Event recording	NVR and SD Card
Interfaces	1 × RJ45 (10/100Mbps), PoE

3. AI ANALYTICS

- Human & vehicle classification [P]
- Line crossing [P]
- Face detection [P]
- Perimeter intrusion [P]

Functions depend on the verified AI package and firmware of the selected camera.

5. VIDEO & NETWORK

Ethernet	PoE Ethernet
Compression	H.265 / H.264
Main stream	30fps; 5MP (2880x1620), 4MP, 3MP, 1080P, 960P, 720P
Sub stream	720P (1280×720), VGA (640×480), QVGA (320×240) @30fps
Mobile stream	VGA (640x480), QVGA (320x240) @ 30fps
Bit rate	256Kbps ~ 8Mbps
Bitrate control	CBR/VBR
Streaming	Unicast / Multicast
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, SMTP,NTP,UPnP,SNMP,HTTPS,FTP,PPPoE
Interoperability	ONVIF Profile S/G/T, RTSP

6. ELECTRICAL & ENVIRONMENTAL

Input power	D12V/POE(IEEE802.3af)
Power - IR off	2.5-3.5W
Power - IR on	4.5-6W
Operating conditions	-35~+60°C/less than ≤ 95% RH
Ingress protection	IP67
Material	Metal
Dimensions	—
Weight	—

ORDERING INFORMATION

SKU	SPC-BLP003	**Model**	SPC-BLP05-F28-A2-G1

Description	5 MP Bullet Camera	Specifications are subject to change without notice.